












ZDYT-T

Self-Propelled Stock Picker (Trinal Mast)

ZDYT3-3.5T / ZDYT3-4.0T / ZDYT3-4.5T


	ZDYT3-3.5T	ZDYT3-4.0T	ZDYT3-4.5T
 S.W.L	300kg	300kg	300kg
Max.occupants	1	1	1
 Working height	5.50m	6.00m	6.50m
Platform floor height	3.50m	4.00m	4.50m
 Overall length	1.56m	1.56m	1.56m
Overall width	0.76m	0.76m	0.76m
Overall height	1.64m	1.81m	1.99m
Platform size	0.93 X 0.70m	0.93 X 0.70m	0.93 X 0.70m
Ground clearance	0.04m	0.04m	0.04m
Wheelbase	1.23m	1.23m	1.23m
Turning radius	0	0	0
 Drive motors	2X24VDC/0.4kw	2X24VDC/0.4kw	2X24VDC/0.4kw
Lifting motor	24VDC/2kw	24VDC/2kw	24VDC/2kw
 Travel speed			
Stowed	4 km/h	4 km/h	4 km/h
Raised	1.1 km/h	1.1 km/h	1.1 km/h
Up/Down speed	20/18sec	22/19sec	24/21sec
 Batteries	2X12V/120Ah	2X12V/120Ah	2X12V/120Ah
Integrated charge	24V/10A	24V/10A	24V/10A
 Gradeability	25%	25%	25%
Maximum slope	1.5°	1.5°	1.5°
 Tyres			
Drive motors	φ 230X80mm	φ 230X80mm	φ 230X80mm
Front wheels	6 in	6 in	6 in
 Weight	642kg	662kg	682kg




Forklift pockets



Self-lock gate on platform



Emergency lowering system



Safety bracket

Standard equipment

- Proportional controls
- Self-closing gate on platform
- Drivable at full height
- Non-marking tyre
- 2WD
- Automatic brake system
- Emergency lowering system
- Emergency stop button
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- All Motion Alarm
- Horn
- Hour meter
- Forklift pockets
- Charger protection
- Flashing beacon

Options

- Overload sensor with alarm
- Platform work lights
- Airline to platform

