


Specifications

MODELS	IWP™-20S		IWP™-25S		IWP™-30S	
	Metric	US	Metric	US	Metric	US
Working height*	8.24 m	26 ft 6 in	9.44 m	30 ft 5 in	11 m	35 ft 6 in
Platform height	6.24 m	20 ft 6 in	7.44 m	24 ft 5 in	9 m	29 ft 6 in
A Horizontal outreach**	61 cm	2 ft	_____	_____	_____	_____
B Height - stowed:						
fully lowered	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in
base raised	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
C Length	1.52 m	5 ft	1.52 m	5 ft	1.52 m	5 ft
D Width - standard base	81 cm	2 ft 8 in	81 cm	2 ft 8 in	_____	_____
wide base	_____	_____	_____	_____	1.02 m	3 ft 4 in
Corner access***	15 cm	6 in	15 cm	6 in	18 cm	7 in



PRODUCTIVITY						
Lift capacity	159 kg	350 lbs	159 kg	350 lbs	159 kg	350 lbs
Platform Dimensions (l/w/h)						
Standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated narrow	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in
Standard fibreglass**	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in

POWER	
AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V / 110 V / 60 Hz or 110/230 Hz worldwide model

WEIGHT****						
Standard base						
AC	564 kg	1,244 lbs	585 kg	1,290 lbs	_____	_____
DC	610 kg	1,345 lbs	630 kg	1,390 lbs	_____	_____
Standard base with outreach option						
AC	612 kg	1,350 lbs	_____	_____	_____	_____
DC	658 kg	1,450 lbs	_____	_____	_____	_____
Wide base						
AC	_____	_____	_____	_____	649 kg	1,430 lbs
DC	_____	_____	_____	_____	694 kg	1,530 lbs
Wide base with outreach option						
AC	658 kg	1,450 lbs	_____	_____	_____	_____
DC	703 kg	1,550 lbs	_____	_____	_____	_____

STANDARDS COMPLIANCE	CN EN280, PB-10-611-03
----------------------	------------------------

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Gated ultra narrow, front and side entry extra-large, and fibreglass platforms are not available with the outreach option.
 *** Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.
 **** Weight will vary depending on options and/or country standards.

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated narrow platform
- Standard fibreglass platform

POWER OPTIONS

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 110 V / 50-60 Hz
- DC power 110/230 V / 50-60 Hz worldwide model
- Power assist option

BASE OPTIONS

- Standard base (IWP™-20S and 25S only)
- Wide base (IWP™-30S only)

STANDARD FEATURES

MEASUREMENTS

IWP™-20S

- 8.24 m (26 ft 6 in) working height
- 6.24 m (20 ft 6 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Outreach option adds 61 cm (2 ft) of horizontal reach
- Up to 159 kg (350 lb) lift capacity

IWP™-25S

- 9.44 m (30 ft 5 in) working height
- 7.44 m (24 ft 5 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Up to 159 kg (350 lb) lift capacity

IWP™-30S

- 11 m (35 ft 6 in) working height
- 9 m (29 ft 6 in) platform height
- 1.02 m (3 ft 4 in) wide base width
- Up to 159 kg (350 lb) lift capacity

PRODUCTIVITY

- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Choose from standard or wide base
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch

STANDARD FEATURES cont.

PRODUCTIVITY cont.

- Ground fault interrupt power receptacle
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks
- Certified load sensor

POWER

- AC power 110 V / 50-60 Hz (not CE)
- AC power 220 V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Gated standard platform
- Gated narrow platform
- Standard fibreglass platform (not available with outreach)
- Outreach option (IWP™-20S only)
- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- Power wheel assist with dual battery package*
- Dual battery package

* Adds 32 cm (12.5 in) to unit length and 129 kg (285 lbs) to unit weight

UK

The Maltings
Wharf Road
Grantham NG31 6BH
UK
Tel: +44 (0)1476 584333
Fax: +44 (0)1476 584334

France

10, ZA de la Croix St. Mathieu
28320 Gallardon
France
Tel: +33 (0)2 37 26 09 99
Fax: +33 (0)2 37 26 09 98

Germany

Finienweg 3
28832 Achim/Bremen
Germany
Tel: +49 (0)4202 8852-0
Fax: +49 (0)4202 8852-25

Spain

Gaià 31, Pol. Ind. Plá d'en Coll
08110 Montcada i Reixac
Barcelona
Spain
Tel: +34 93 572 50 90
Fax: +34 93 572 50 91

Scandinavia

Aröds industriväg 34
422 43 Hisings Backa
Sweden
Tel: +46 31 57 51 00
Fax: +46 31 57 51 04

Middle East

Terex Middle East
PO Box 282325, Dubai
U.A.E.
Tel: +971 4 885 8030
Fax: +971 4 885 6364
Email: awp.infome@terex.com

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, WA
USA 98073-9730
Tel: +1 425 881-1800
Fax: +1 425 883-3475

Email: AWP-InfoEurope@terex.com

Distributed By: