

HB-1030CE



Hy-Brid
Lifts

HB-1030CE



The HB-1030CE's compact size and ease of operation makes it desirable for use in hospitals, clinics, libraries, office buildings; anyplace where quiet operation is a must. With our long list of standard design features, the HB-1030CE is the correct choice when buying or hiring a lift in this height/capacity

Our simple, straightforward design!



The self-contained lift hydraulic system (shown above) is designed for trouble-free operation. The HB-1030CE features fully-proportional dual-motor electric drive and electric steering, giving the operator extra-long duty cycles between charges.



The HB-1030CE utilizes a highly efficient 24 vdc electrical system and includes an integrated battery charger with charge level indicator, descent and tilt alarms, palm button emergency stops, remote raise/lower station and key switch. Our open bay design provides direct access to all critical components. This innovative design feature reduces repair time, helping keep costs down.



Non-marking tires, with a unique dual-wheel front steering system eliminates floor scuffing and carpet buckling, helping prevent damage to sensitive and/or decorative flooring materials. The HB-1030CE's design includes pothole protection and meets or exceeds applicable OSHA, EN280, and ANSI A92.6-1999 safety standards.

30cm step height provides easy access!

The HB-1030CE has an incredibly low 60cm platform height. This provides easy-on/easy-off, all-day access for the operator.

With a platform size of 64cm x 152cm, a platform extension of 76cm and a machine weight of 600kg, (minimum floor load - 4.8kPa), this lift can safely travel on limited capacity mezzanines, computer floors, and is light enough to utilize most personnel-rated building elevators.



HB-1030CE Specifications

Platform Capacity (total)	340.2 kg
Rated Occupancy	2-persons
Platform Working Height	4.87 m
Platform Height (maximum)	3 m
Platform Height (minimum)	60 cm
Platform Size	64 cm x 152 cm
Platform Extension	76 cm
Weight	680 kg
Floor Loading (min. wheel load)	504.5 kPa
Floor Loading (max. wheel load)	756.8 kPa
Floor Loading (min. machine load)	5.43 kPa
Floor Loading (max. machine load)	8.14 kPa
Height	179 cm
Width	76 cm
Length	176.5 cm
Gradeability	30 degree
Inside Turning Radius	53 cm
Drive Speed	0-1.12 m/s
Lift Speed Up/Down	15/22 s
Ground Clearance	7.5 cm

Hy-Brid Lifts

CUSTOM EQUIPMENT

2647 Hwy 175 • Richfield, WI • 53076
866-334-0756 • www.customequipmentlifts.com

The photographs and drawings in this brochure are for illustrative purposes only. The continuous improvement of our products is policy. Product specifications are subject to changes without notice. Contact Custom Equipment, Inc. for the latest product specifications.