

SJIII SERIES

MODEL	WORK HEIGHT	Raised Platform Height	Lowered Platform Height	O/A Width	O/A Length	Stowed Height Railings Up	Stowed Height Railings Down	% Gradeability Ω	CAPACITY kg Σ	# OF PERSONS	PLATFORM SIZE (Inside Dimension)	TRAVEL SPEED km/h	LIFT TIME (sec) †	WEIGHT kg Σ
-------	-------------	------------------------	-------------------------	-----------	------------	---------------------------	-----------------------------	------------------	---------------	--------------	----------------------------------	-------------------	-------------------	-------------

C O M P A C T S														
3215	6,4m	4,6m	0,88m	0,81m	1,78m	1,99m	1,63m OPT	23%	227kg	2	0,66 x 1,57m	3,2km/h	23	1090kg
3219	7,6m	5,8m	0,99m	0,81m	1,78m	2,11m	1,75m OPT	23%	227kg	2	0,66 x 1,57m	3,2km/h	25	1170kg

C O N V E N T I O N A L S														
3220	7,9m	6,1m	0,97m	0,84m	2,32m	2,08m	1,72m OPT	25%	408kg	2	0,71 x 2,13m	3,2km/h	33	1583kg
3226	9,7m	7,9m	1,15m	0,84m	2,32m	2,27m	1,94m	25%	227kg	2	0,71 x 2,13m	3,2km/h	56	1864kg
4620	7,9m	6,1m	0,97m	1,17m	2,31m	1,96m	1,71m OPT	25%	590kg	3	1,07 x 2,11m	3,2km/h	33	1860kg
4626	9,7m	7,9m	1,14m	1,17m	2,31m	2,15m	1,87m	25%	454kg	3	1,07 x 2,11m	3,2km/h	55	2130kg
4632	11,6m	9,7m	1,23m	1,17m	2,31m	2,24m	1,96m	25%	318kg	2	1,07 x 2,11m	3,2km/h	59	2300kg
6826	9,7m	7,9m	1,27m	1,73m	2,52m	2,37m	1,99m	25%	454kg	3	1,53 x 2,05m	3,2km/h	65	2440kg
6832	11,6m	9,7m	1,4m	1,73m	2,52m	2,51m	2,13m	25%	454kg	3	1,53 x 2,05m	3,2km/h	60	2700kg

M E T R I C S														
3220	7,9m	6,1m	0,97m	0,84m	2,32m	2,08m	1,75m	25%	408kg	2	0,71 x 2,13m	3,2km/h	33	1583kg
3226	9,7m	7,9m	1,15m	0,84m	2,32m	2,27m	1,94m	25%	227kg	2	0,71 x 2,13m	3,2km/h	56	1864kg

† Lift times with rated load

Ω Gradeability calculated with 1 operator capacity

Σ Some capacities are reduced and overall machine weights increased when equipped with deck extensions - consult factory for details.

Models	Compacts		Conventionals							Metrics	
	3215	3219	3220	3226	4620	4626	4632	6826	6832	3220	3226

S T A N D A R D E Q U I P M E N T												
Driveable at Full Height	•	•	•	•	•	•	•	to 8m	•	to 8m	•	•
Dual Parking Brakes	•	•	•	•	•	•	•	•	•	•	•	•
Universal Battery Charger	•	•	•	•	•	•	•	•	•	•	•	•
Color Coded and Numbered Wiring System	•	•	•	•	•	•	•	•	•	•	•	•
Foam Filled Tires												
Solid Rubber, Non-Marking Tires	•	•	•	•	•	•	•	•	•	•	•	•
0.9m Roll Out Deck Extension	•	•	•	•	•	•	•	•	•	•	•	•
Swing Out Trays, for easy access	•	•	•	•	•	•	•	•	•	•	•	•
Joystick Proportional Control for Drive/Lift	•	•	•	•	•	•	•	•	•	•	•	•
Tilt Alarm with Drive/Lift Cut Out	•	•	•	•	•	•	•	•	•	•	•	•
Wiring for AC Outlet	•	•	•	•	•	•	•	•	•	•	•	•
Lanyard Attachments Points	•	•	•	•	•	•	•	•	•	•	•	•
Rigid Steel Scissor Guards												
Hinged Railing System				•	•	•	•	•	•	•	•	•
Lowering Warning System	•	•	•	•	•	•	•	•	•	•	•	•
Overload Sensing System	•	•	•	•	•	•	•	•	•	•	•	•
Forklift Pockets/Tie Downs/Lifting Lugs	•	•	•	•	•	•	•	•	•	•	•	•
Pothole Protection	•	•	•	•	•	•	•	•	•	•	•	•
Operator Horn	•	•	•	•	•	•	•	•	•	•	•	•
DC Power (V DC)	24	24	24	24	24	24	24	24	24	24	24	24
Base Controls	•	•	•	•	•	•	•	•	•	•	•	•
Spring Loaded Half Height Gate	•	•	•	•	•	•	•	•	•	•	•	•

O P T I O N A L E Q U I P M E N T												
Spring Loaded Full Gate entry	•	•	•	•	•	•	•	•	•	•	•	•
1.8m Power Deck Extension												
1.5m Power Deck Extension												
Flashing Light	•	•	•	•	•	•	•	•	•	•	•	•
Hinged Railing System	•	•	•	•	•	•	•	•	•	•	•	•
"Shop Air" Line Air to Platform	•	•	•	•	•	•	•	•	•	•	•	•
Non-marking Foam Filled Tires												
All Motion Alarm	•	•	•	•	•	•	•	•	•	•	•	•
Rigid Steel Scissor Guards	•	•	•	•	•	•	•	•	•	•	•	•

STANDARD FEATURES
STANDARD/OPTIONAL EQUIPMENT
SPECIFICATIONS