MB20J/MB26J MAST BOOM LIFTS



- Versatile electric mast booms
- Ultra-narrow for use in confined spaces
- Superb working envelope including "up & over" capabilities
- Simple to operate and maintain
- Ideal for retail and warehouse applications ______



MAST BOOM LIFTS

DIMENSIONS	MB20J	MB26J
Max. working height	8.0m	10.0m
Max. platform height	6.0m	8.0m
Max. working outreach	2.6m	3.0m
Platform size	0.78m x 0.73m	0.78m x 0.73m
Overall width (A)	0.81m	1.0m
Stowed length (C)	2.43m	2.8m
Stowed height (B)	1.98m	1.98m
Ground clearance	100mm	100mm

PERFORMANCE

Platform capacity (SWL)	215kg	215kg
Max. drive height	6.0m	8.0m
Max. drive speed (stowed)	3.3km/h	3.3km/h
Max. drive speed (elevated)	0.6km/h	0.6km/h
Jib length	1.02m	1.4m
Jib arc	130°	120°
Mast rotation (non-continuous)	360°	360°
Raise/lower time	54/26sec	56/27sec
Gradeability	25%	25%
Inside turning radius	0.3m	0.3m
Outside turning radius	1.85m	2.1m
Tyres	343-285 non-marking	
Drive system	electro/hydraulic	

POWER

Power source


4 x 6V x 375 AH batteries

2,660kg


WEIGHT

2,590kg

WORKING ENVELOPE



MB20J/MB26J



STANDARD FEATURES

- Proportional one-hand controls •
- Ultra-tight inside turning radius •
- Tilt alarm •
- Power line to platform (no sockets) •
- 2 persons + equipment capacity indoors •
- 1 person + equipment capacity outdoors •
- Solid non-marking tyres •
- Ground control station
- Self-seeking automatic charger •
- Automated battery top up
- CE approved •

OPTIONS

- Special paint colours •
- Flashing amber beacon •
- Environmental green oil •



Vigo Centre, Birtley Road, Washington, Tyne & Wear, NE38 9DA, U.K.

t: +44 (0) 845 1550 057 e: sales@snorkellifts.com

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance.