

Specifications*

ITEM	SL-26N	SL-30N
Platform Size (Inside Toeboards)		
Standard	57.5 in. x 141.5 in. [1.46 m x 3.59 m]	57.5 in. x 166.25 in. [1.46 m x 4.22 m]
w/Extension	57.5 in. x 181.5 in. [1.46 m x 4.61 m]	N/A
Max. Platform Capacity		
Standard	1250 lbs. [567 kg]	1000 lbs. [363 kg]
w/Extension	1250 lbs. [567 kg]	N/A
on Extension	500 lbs. [110 kg]	N/A
Max. No. Of occupants		
Standard	5 people	4 people
on Extension	2 people	N/A
Height		
Working Height	32 ft. [9.75 m]	36 ft. [10.97 m]
Max. Platform Height	26 ft. [7.93 m]	30 ft. [9.14 m]
Min. Platform Height	59 in. [1.5 m]	59 in. [1.5 m]
Dimensions		
Weight	Electric 5,160 lbs. [2341 kg] Kohler Gas 4,910 lbs. [2227 kg] Kubota Gas 5,040 lbs. [2286 kg] Kubota Diesel 5,100 lbs. [2313 kg]	Electric 5,470 lbs. [2481 kg] Kohler Gas 5,220 lbs. [2368 kg] Kubota Gas 5,350 lbs. [2427 kg] Kubota Diesel 5,410 lbs. [2454 kg]
Overall Width	66 in. [1.68 m], with standard tires	66 in. [1.68 m], with standard tires
Overall Height	94.5 in. [2.40 m]	94.5 in. [2.40 m]
Overall Length	149 in. [3.79 m]	173 in. [4.39 m]
Drivable Height	26 ft. [9.75 m]	30 ft. [10.97 m]
Surface Speed		
Platform Lowered: Gas/Diesel	0 to 3.1 mph [0 to 5.0 km/h]	0 to 3.1 mph [0 to 5.0 km/h]
Electric	0 to 2.6 mph [0 to 4.2 km/h]	0 to 2.6 mph [0 to 4.2 km/h]
Platform Raised: Gas/Diesel	0 to .5 mph [0 to .8 km/h]	0 to .5 mph [0 to .8 km/h]
Electric	0 to .5 mph [0 to .8 km/h]	0 to .5 mph [0 to .8 km/h]
System Voltage	Gas/Diesel: 12 Volt DC Electric: 24 Volt DC	Gas/Diesel: 12 Volt DC Electric: 24 Volt DC
Battery Charger (Electric only)	40 Amp 110 V 60 Hz (40 Amp 220 V 50 Hz, Optional)	40 Amp 110 V 60 Hz (40 Amp 220 V 50 Hz, Optional)
Hydraulic Tank Capacity	12 Gallons [45.5 l]	12 Gallons [45.5 l]
Maximum Hydraulic System Pressure	2500 psi [172 bar]	2500 psi [172 bar]
Hydraulic Fluid		
Normal Use (>32° F [0° C])	ISO #46	ISO #46
Low Temp. Use (-10 to 32° F [-23 to 0° C])	5W-20 Motor Oil	5W-20 Motor Oil
Lift System	One Single Stage Lift Cylinder	One Single Stage Lift Cylinder
Lift Speed		
Gas/Diesel	Raise, 20 sec./Lower, 35 sec.	Raise, 23 sec./Lower, 35 sec.
Electric	Raise, 33 sec./Lower, 35 sec.	Raise, 33 sec./Lower, 35 sec.
Power Source	Two 4HP Electric Motors, Eight 6V 220 Amp/Hour Batteries, 20 HP Kohler Magnum, 20 HP Kubota WG750, 20 HP Kubota D905 (Diesel)	Two 4HP Electric Motors, Eight 6V 220 Amp/Hour Batteries, 20 HP Kohler Magnum, 20 HP Kubota WG750, 20 HP Kubota D905 (Diesel)
Drive Control	Proportional	Proportional
Control System	Proportional Joystick Controller with Interlock	Proportional Joystick Controller with Interlock
Horizontal Drive	Dual Rear Wheel, Hydraulic Motors	Dual Rear Wheel, Hydraulic Motors
Tires	B78-13ST Slab, 50 psi	B78-13ST Slab, 50 psi
Parking Brake	Spring Applied, Hydraulic Release	Spring Applied, Hydraulic Release
Turning Radius (inside)	9 ft. 9 in. [2.97 m]	9 ft. 9 in. [2.97 m]
Maximum Gradeability	Gas/Diesel: 30% [16°] Electric: 25% [14°]	Gas/Diesel: 30% [16°] Electric: 25% [14°]
Wheel Base	100 in. [2.54 m]	100 in. [2.54 m]
Guardrails	43.5 in. [1.11 m] high, Fold Down with Gate	43.5 in. [1.11 m] high, Fold Down with Gate
Toeboard	6 in. [152 mm] High	6 in. [152 mm] High

* Specifications subject to change without notice.

Meets or exceeds all applicable requirements of OSHA and ANSI A92.6-1990

Refer to Service Manual for complete parts and service information.

FOR MORE INFORMATION

Available from:


Access Platform Sales Ltd

Leewood Business Park, Upton, Huntingdon, PE28 5YQ
Tel: +44 (0) 1480 891251 Fax: +44 (0) 1480 891162
Website: www.accessplatforms.co.uk
Email: sales@accessplatforms.co.uk

Local Distributor: