

DSKE2-12V Scheibenbutler

450 kg
↓
↑
max.

WienoldLIFTE
since 1987

The **DSKE2-12V** is a Vacuum Glas Lifter based on a two circle System. In case of a failure in one circle, the second circle will hold the glass safe in position.

Especially for the assembly of glas panels with different formats and weights the DSKE2 is offering helpfull flexibility to fit the sizes and weights of the panes by easy handling.

The basic unit consists of 4 suction cups. Two additional suction cups allow the system to be adapted as an extension for long narrow panes. The separate suction plates can also be arranged in a cross-shaped configuration for rectangular and square formats.

That reduces glass breakage risks significantly by increasing the stability for various formats.

Overhead mounting will be also easily done, because the unit is manually tiltable up to 90°. The system is also rotatable by 360°.

The scope of supply includes a carrier with casters for all compontens to safe space in stock.

The safe and easy way of glass handling: **DSKE2**.



Technical Data

Payload:	450 kg (with 6 Suction Cups) 300 kg (with 4 Suction Cups)
Frame:	4 Suction Cups in a row
Set up:	4 + 1, 4 + 2 in Line or Cross Shape
Operation:	12V Pump incl. Charger Unit
Functions:	Absorb/Detach by Remote Control
Rotate:	360° manually
Tilting:	90° manually
Incl.:	Charger Unit, Cable Remote Control, Carrier with Casters
Weight:	approx. 60 kg (with 6 Suction Cups)

Fits to: WLU-P
SLK
GML
MFC



WienoldLIFTE
since 1987

Norbert Wienold GmbH
Material- und Personenlifte

Industriegebiet Waldstr. 35 a
D-48488 Emsbüren | Germany

Phone +49 59 03 - 93 94-0
Fax +49 59 03 - 93 94-50

eMail: info@wienold-lifte.de
Wienold-LIFTE.de



Service Stations:

München | Leverkusen | Walsrode | Brandenburg | Emsbüren



Wienold BRANDS
GML-Series
WLU-Series
SLK-Series
MFC-Series
Materiallifts • Glaslifts • Mini Floor Cranes