

DIESEL RT SCISSOR Lift

SR0818D (SR2669D) **NEW PRODUCT**

SR1018D (SR3369D) / SR1218D (SR4069D)



HIGHLIGHTS

LGMG SR18D Series rough terrain scissor lifts are specifically built for tough construction sites with four-wheel drive and fantastic gradeability. High load capacities with compact design provide a great combination for the larger working area and greater maneuverability through rough terrain job sites.

- High capacity, large platform with compact design maximises productivity.
- Powerful diesel engine and four-wheel drive make the machine ideal for varying conditions.
- Oscillating axles with great gradeability provide better performance on rough terrain job sites.
- Optional hydraulic outriggers deliver better stability on uneven ground.
- Intelligent self-diagnostic system for quick troubleshooting.

SPECIFICATIONS

MODELS	NEW SR0818D (SR2669D)		SR1018D (SR3369D)		SR1218D(SR4069D)	
Measurements	Metric	US	Metric	US	Metric	US
Working Height Max.	9.7m	31.8ft	11.7m	38.4ft	13.9m	45.9ft
A Platform Height-Raised	7.7m	25.26ft	9.7m	31.8ft	11.9m	39ft
B Platform Height-Stowed	1.41m	4.62ft	1.41m	4.62ft	1.56m	5.12ft
C Platform Length	2.79m	9.15ft	2.79m	9.15ft	2.79m	9.15ft
D Platform Width	1.6m	5.25ft	1.6m	5.25ft	1.6m	5.25ft
E Overall Length	3.11m	10.2ft	3.76m	12.33ft	3.76m	12.33ft
F Overall Width	1.79m	5.87ft	1.79m	5.87ft	1.79m	5.87ft
G Overall Height-Rails Up	2.58m	8.46ft	2.55m	8.37ft	2.7m	8.86ft
Overall Height-Rails Down	1.89m	6.2ft	1.89m	6.2ft	2.04m	6.69ft
H Extension Deck	1.52m	4.99ft	1.52m	4.99ft	1.52m	4.99ft
I Wheelbase	2.29m	75.1in	2.29m	75.1in	2.29m	75.1in
Ground Clearance-Center	0.23m	0.75ft	0.23m	0.75ft	0.23m	0.75ft
PRODUCTIVITY						
Platform Occupants Max. (in/out)	4 / 4	4 / 4	4 / 2	4 / 2	3 / 2	3 / 2
Platform Capacity	680kg	1499lbs	454kg	1000lbs	365kg	805lbs
Platform Capacity-Extension	140kg	310lbs	140kg	310lbs	140kg	310lbs
Drive Height	Full Height		Full Height		Full Height	
Gradeability-Stowed	40%		35%		35%	
Turning Radius-Outside	4.75m	15.6ft	4.75m	15.6ft	4.75m	15.6ft
Raise/Lower Speed	35 / 30s		39 / 46s		61 / 55s	
Brakes	Four-wheel Brake		Four-wheel Brake		Four-wheel Brake	
Drive Mode	4x4		4x4		4x4	
Tires Type	Foam-filled		Foam-filled		Foam-filled	
Tires Size	663x283mm	26x12in	663x283mm	26x12in	663x283mm	26x12in
POWER						
Power Source	Kubota D1105 18.5kw/24.8hp		Kubota D1105 18.5kw/24.8hp		Kubota D1105 18.5kw/24.8hp	
Fuel Tank Capacity	53 L	14gal	53 L	14gal	53 L	14gal
HYDRAULIC SYSTEM						
Hydraulic Oil Capacity	50 L	13.21gal	70 L	18.5gal	70 L	18.5gal
WEIGHT						
Machine Weight with Outriggers(CE/ANSI)	4054kg	8937lbs	4330kg	9768lbs	5080kg	11176lbs
Machine Weight without Outriggers(Optional)	3700kg	8157lbs	/	/	/	/

