

nifty

HR15 2x4 4x4 HYBRID

**SELF PROPELLED
ACCESS PLATFORM**



15.6m (51ft 6in)
Working height

9.2m (30ft 6in)
Unrestricted working
outreach at 225kg

**Proportional
Multi-Function Control**
Fast & precise operation

GVW From Only 4,300kg
Lowest weight in its class

SiOPS® as Standard
Award winning
operator protection

**180° Platform Rotation
& 150° Fly-Boom**
Improved access to
applications



niftylift.com



nifty HR15

The super-low-weight **Height Rider 15 (HR15)** is available as a Diesel powered 2-wheel-drive (2x4) or 4-wheel-drive (4x4), or as a Hybrid powered 4x4 and offers one of the best working envelopes in its class. Its compact base allows it to manoeuvre easily in restricted areas and its very low overall weight helps to minimise transportation costs. The 1.80m wide cage provides more room for materials and tools and a 150° fly-boom with 180° cage rotation helps to increase accuracy when positioning.


The **2x4** version offers a cost effective and economical option to anyone looking to minimise running costs.

The **4x4** version offers maximum traction and gradeability, making it ideal for rough or uneven ground.

The **Hybrid** version offers maximum efficiency and environmental consciousness. An electric only mode allows zero-emission operation for clean or noise sensitive applications while the Hybrid mode with catalytic converter minimises fuel consumption and exhaust emissions, and with Diesel 'Re-Gen', is capable of running 24/7 for unbeatable utilisation.

SAFETY FEATURES

- SiOPS®
- Automatic Fail-Safe Brakes
- Tilt Alarm
- Lock Valves on all Hydraulic Cylinders
- Solid Tyres
- Powered Auxiliary Descent
- Dual Harness Points
- Manual Recovery with Hand Pump
- CE Mark
- Dual Controls (Platform & Base)



The tough, impact-resistant composite base and larger cross-section steel rails of the HR15's **ToughCage** give extra strength and durability and the multi award winning **SiOPS®** provides additional operator protection.

SPECIFICATIONS

Working Height	15.60m	51ft 6in
Platform Height	13.60m	45ft
Working Outreach	9.20m	30ft 6in
Slew	360°	
Fly-Boom Arc	150°	
Width	2.00m	6ft 7in
Height	2.15m	7ft
Length - Stowed	5.10m	16ft 9in
- Overall	6.50m	21ft 4in
Minimum Weight - 2x4	4,300kg*	9,500lbs*
- 4x4	4,500kg*	9,900lbs*
- Hybrid	4,700kg*	10,360lbs*
Turning Radius - Outside	3.70m	12ft 2in
Platform Rotation	180°	
Platform Capacity	225kg	500lbs
Platform Size	1.80m x 0.85m	5ft 11in x 2ft 9in
Drive Speed - 2x4	4.1km/h	2.5mph
- 4x4	6.6km/h	4.1mph
Gradeability	35% (19°) - 2x4	45% (24°) - 4x4
Power System - 2x4	Diesel (Kubota 722 - 18Hp/14kW)	
- 4x4	Diesel (Kubota 1105 - 25Hp/18.5kW)	
- Hybrid	Battery & Diesel (Kubota 722 - 18Hp/14kW)	

* Weights may vary according to specification, please confirm before ordering.

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

Supplied by:

Manufacturers of trailer mounted, self propelled and vehicle mounted platforms.

NIFTYLIFT LTD
Fingle Drive
Stonebridge
Milton Keynes
MK13 0ER
England

www.niftylift.com

e.mail: info@niftylift.com

Tel.: +44 (0)1908 223456

Fax.: +44 (0)1908 312733

