

Specifications

Models	GL-4		GL-8		GL-10		GL-12	
Measurements	Metric	US	Metric	US	Metric	US	Metric	US
A Height - stowed ^{1,2,3}	1.72 m	5 ft 7.5 in	1.72 m	5 ft 7.5 in	2.00 m	6 ft 6.5 in	2.31 m	7 ft 7 in
maximum forks down	1.26 m	4 ft 1.5 in	2.50 m	8 ft 3 in	3.01 m	9 ft 10.5 in	3.66 m	12 ft
maximum forks up	1.80 m	5 ft 11 in	3.06 m	10 ft .5 in	3.56 m	11 ft 8 in	4.20 m	13 ft 9.5 in
minimum forks down	9 cm	3.5 in	9 cm	3.5 in	5 cm	2 in	5 cm	2 in

Standard Base

A Length - stowed	30 cm	1 ft	30 cm	1 ft	—	—	—	—
operating	88 cm	2 ft 10.75 in	88 cm	2 ft 10.75 in	—	—	—	—
C Width: outside	63 cm	2 ft 0.75 in	63 cm	2 ft 0.75 in	—	—	—	—
Weight - standard caster options	51 kg	113 lbs	60 kg	132 lbs	—	—	—	—
pneumatic caster options	53 kg	117 lbs	62 kg	136 lbs	—	—	—	—

Straddle Base

Length - stowed	49 cm	1 ft 7.25 in	49 cm	1 ft 7.25 in	49 cm	1 ft 7.25 in	49 cm	1 ft 7.25 in
operating	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in
Width - stowed ⁴	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in
maximum ⁴	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in
maximum inside	91 cm	3 ft	91 cm	3 ft	91 cm	3 ft	91 cm	3 ft
Weight - standard caster options	57 kg	126 lbs	66 kg	145 lbs	68 kg	149 lbs	70 kg	154 lbs
pneumatic caster options	59 kg	130 lbs	68 kg	149 lbs	69 kg	153 lbs	72 kg	158 lbs
4-point caster option A	62 kg	137 lbs	72 kg	158 lbs	73 kg	162 lbs	76 kg	167 lbs
4-point caster option B	63 kg	139 lbs	73 kg	160 lbs	75 kg	164 lbs	77 kg	169 lbs

Counterweight Base

Length - operating	72 cm	2 ft 4.5 in	72 cm	2 ft 4.5 in	72 cm	2 ft 4.5 in	—	—
Width - stowed ⁴	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	—	—
maximum ⁴	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	—	—
maximum inside	91 cm	3 ft	91 cm	3 ft	91 cm	3 ft	—	—
Weight - standard caster options	178 kg	392 lbs	186 kg	411 lbs	196 kg	433 lbs	—	—

Productivity

Load height minimum	9 cm	3.5 in	9 cm	3.5 in	9 cm	3.5 in	9 cm	3.5 in
Ground clearance - center ^{1,2,3}	2 cm	0.75 in	2 cm	0.75 in	2 cm	0.75 in	2 cm	0.75 in
Average cranks - standard winch	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft
Fork length	57 cm	1 ft 10.5 in	57 cm	1 ft 10.5 in	57 cm	1 ft 10.5 in	57 cm	1 ft 10.5 in
Fork width	52 cm	1 ft 8.5 in	52 cm	1 ft 8.5 in	52 cm	1 ft 8.5 in	52 cm	1 ft 8.5 in
Load platform length	58 cm	1 ft 11 in	58 cm	1 ft 11 in	58 cm	1 ft 11 in	58 cm	1 ft 11 in
Load platform width	56 cm	1 ft 10 in	56 cm	1 ft 10 in	56 cm	1 ft 10 in	56 cm	1 ft 10 in
Load capacity at								
12 in (30 cm) load center	227 kg	500 lbs	181 kg	400 lbs	159 kg	350 lbs	159 kg	350 lbs
Boom length	51 cm	20.19 in	51 cm	20.19 in	51 cm	20.19 in	51 cm	20.19 in
Boom attachment points	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in

Power

Power source reversible standard winch


Standards Compliance EU Directive: 2006/42/EC (Machinery)

¹ The 25 cm (10 in) pneumatic rear wheel option will add 2.5 cm (1 in) to these specifications.

² The counterweight base will add 2.5 cm (1 in) to these specifications.

³ The 4-point caster option B will add 2.5 cm (1 in) to these specifications.

⁴ Outside dimensions.



Features

Standard Features

Measurements

GL™-4

- 1.80 m (5 ft 11 in) maximum lifting height
- Up to 227 kg (500 lbs) load capacity

GL-8

- 3.06 m (10 ft .5 in) maximum lifting height
- Up to 181 kg (400 lbs) load capacity

GL-10

- 3.56 m (11 ft 8 in) maximum lifting height
- Up to 159 kg (350 lbs) load capacity

GL-12

- 4.20 m (13 ft 9.5 in) maximum lifting height
- Up to 159 kg (350 lbs) load capacity

Productivity

- Portable and compact design
- Lightweight durable aluminum construction
- Durable standard steel forks
- 20 cm (8 in) non-marking rear wheels and 5 cm (2 in) dual wheel front swivel casters (standard and straddle base only)
- 12 cm (5 in) rear swivel casters with side brakes and 10 cm (4 in) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

Power

- Standard winch
- Reversible winch handle for easy storage

Easily Configured To Meet Your Needs

Productivity & Fork Options

- Standard forks
- Load platform
- Boom

Power

- Standard winch

Base Options

- Standard base (GL-4, -8 only)
- Straddle base (all units)
- Counterweight base (GL-4, -8, -10 only)

Wheel/Caster Options

Straddle and standard base

- 20 cm (8 in) non-marking rear wheels
- Pneumatic rear tyre option
- 5 cm (2 in) dual wheel front swivel casters

Counterweight base

- 12 cm (5 in) rear swivel casters with side brakes
- 10 cm (4 in) fixed front wheels

Straddle base

- 4 point caster option A: 10 cm (4 in) rear swivel casters, 5 cm (2 in) front swivel casters
- 4 point caster option B: 12 cm (5 in) rear swivel casters, 6.5 cm (2.5 in) front swivel casters

Options & Accessories

Productivity

- Load platform
- Boom
- Aluminum ladder (standard and straddle base only) ⁽¹⁾
- Pneumatic rear tyre option (standard and straddle base only)
- Foot-release brake (standard and straddle base only)
- 4 point caster option (straddle base only)

Power

- Heavy duty reversible winch
- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle bases



⁽¹⁾ Available aftermarket only

07/15 Part No. B109382UK



Access Platform Sales

Leewood Business Park, Upton, Huntingdon, Cambridgeshire PE28 5YQ, United Kingdom. Tel: 0845 108 4000 Fax: 01480 891162 Email: sales@iapsgroup.com www.iapsgroup.com

Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico · Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed maybe trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2015 Terex Corporation.