

SAFETY FIRST...

ALWAYS



**Be confident
with Outrigger Pads**

OUTRIGGER PADS



01480 891251



The best outrigger pads in the world are now available from APS – the UK's largest independent access platform sales specialist.

Available in a wide range of sizes to suit your equipment.



Spider Type Boom Lifts




Mini Cranes



Scissor Lifts



Concrete Pumps



Mobile Cranes



Lorry Loaders



Ground Mats – protect the surface and prevent your equipment from sinking into the ground. Lightweight, easy to handle and available in a range of sizes from **2000mm x 800mm x 15mm** to **6000mm x 1000mm x 20mm**.



Stillages – for easy and convenient storage of road mats.
Available to suit 2m or 3m mats.



Stowage Boxes – Stainless steel stowage brackets available for **300, 400, 500 and 600mm pads**



Slider Outrigger Shoes – Helps aid set up – slides onto the outrigger/stabiliser leg allowing you to move your machine without repositioning your pads.
Available in three sizes.



Containershield® – Prevents surface damage and corrosion as well as reduces noise when containers are moved.
Used extensively in waste recycling centres.



Ramps – suitable for up to 100 Ton per set load bearing on wheel or track mounted vehicles.
Durable and withstands diesel and most chemical spills.




Pad Dimensions

From
30cm x 30cm
up to **1m x 1m**
and up to **70 tonne**



Fitted with
1 lash up to 25kg
2 lashes above 25kg
Graded chain
lashes available

Outrigger



From
80cm to
120cm diameter
and up to **120 tonne**

Dimensions

300 x 300 x 30 mm
400 x 400 x 30 mm
300 x 300 x 40 mm
400 x 400 x 40 mm
500 x 500 x 40 mm
600 x 600 x 40 mm
800 x 800 x 40 mm
900 x 900 x 40 mm
1000 x 1000 x 40 mm
400 x 400 x 50 mm
500 x 500 x 50 mm
600 x 600 x 50 mm
700 x 700 x 50 mm
800 x 800 x 50 mm
900 x 900 x 50 mm
1000 x 1000 x 50 mm
400 x 400 x 60 mm
500 x 500 x 60 mm
600 x 600 x 60 mm
800 x 800 x 60 mm
900 x 900 x 60 mm
1000 x 1000 x 60 mm

Weight

2.6 kg
4.7 kg
3.4 kg
6.1 kg
9.4 kg
13.5 kg
24.3 kg
30.8 kg
38.0 kg
7.6 kg
11.9 kg
17.1 kg
23.3 kg
30.4 kg
38.5 kg
47.5 kg
9.1 kg
14.1 kg
20.3 kg
36.5 kg
46.2 kg
57.0 kg

Vertical Jack Cap.

8 tonne
10 tonne
9 tonne
12 tonne
18 tonne
22 tonne
35 tonne
38 tonne
35 tonne
15 tonne
20 tonne
25 tonne
28 tonne
40 tonne
42 tonne
50 tonne
20 tonne
22 tonne
30 tonne
45 tonne
48 tonne
70 tonne

Dimensions

Ø 990 x 40 mm
Ø 990 x 50 mm
Ø 990 x 60 mm
Ø 1190 x 60 mm
Ø 1190 x 80 mm

Weight

30 kg
37 kg
45 kg
64 kg
85 kg

Vertical Jack Cap.

28 tonne
50 tonne
60 tonne
90 tonne
120 tonne

NOLIM OUTRIGGER PADS

ARE BUILT TO LAST

Prevents machinery from sinking into the ground

Strong, lightweight, high quality HMPE that doesn't absorb moisture and will not break or splinter

Extensively tested by world renowned TÜV





parts@accessplatforms.co.uk

www.accessplatforms.co.uk

[illegible]